






PROJECT	TYPE	CATALOG NUMBER
---------	------	----------------



DESCRIPTION

- Four light square recessed accent / downlight - large size
- All steel 18GA construction with powder coat finish
- 1" Trim flange with 13.00" x 13.00" open aperture
- Trim flange removable for maintenance
- Vent holes for cooler operating temperature
- Trim features deep sleeve to conceal inner components
- **Ceiling Cut-Out - 13.12" x 13.12"**

LAMPS (not included)








- 120V PAR30 Halogen 75W max - Derate Labels Available
- PAR30MH 20W, 39W or 70W
- PAR30 20W LED Retrofit
- Double gimbal lamp holder with up to 40° x 40° tilt aiming
- Accepts up to 2 or more optical accessories, dependent on lamp
- Trim mounted double gimbal standard with optional single gimbal flush yoke, regressed yoke or adjusting retractable yoke

ORDERING INFO

SERIES	WATTAGE / LAMP	LAMP ASSEMBLY	POWER SUPPLY	VOLTAGE	FINISH	OPTION
MF3QDN-T MULTIFORMS MF300 Series Recessed 4-Light Square Straight Aperture Adjustable Accent Trimmed Fixture New Construction Housing	040PR30X PAR30 40W max	TD Trim Mounted Double Gimbal	NA None - Line voltage lamps	1 120V 2 277V	BB Black WW White WB White Trim / Black Interior SS Silver SB Silver Trim / Black Interior XX Custom	CP Chicago Plenum
	050PR30X PAR30 50W max	YG Yoke Gimbal Flush to Ceiling Line	EB Electronic Metal Halide Ballast			
	075PR30X PAR30 75W max	GG Regressed Yoked Gimbal*				
	020CR30X PAR30MH 20W 039CR30X PAR30MH 39W 070CR30X PAR30MH 70W	RG Retractable Yoked Gimbal				
MF3QDN-T	020PR30X PAR30 20W LED Retrofit	* Required to enable flush appearance with snoot accessory				

Ordering Example: **MF3QDN-T-075PR30X-TD-NA-1-BB-CP**




OPTICAL ACCESSORY	DESCRIPTION	LIGHT SOURCE
		LARGE
		<ul style="list-style-type: none"> • PAR30 / PAR30CMH • T4G8.5 • T6G12 • AR111 / CDMR111 • 111mm LED
	Clear Lens	OPTD-CLR
	Clear Lens - LED Film	OPTD-L-CLR
	UV Lens	OPTD-UVL
	Hex Cell Louver	OPTD-HXL
	Diffusion Lens	OPTD-DFL
	Diffusion Lens - LED Film	OPTD-L-DFL
	Linear Spread Lens	OPTBD-LSL
	Linear Spread Lens - LED Film	OPTD-L-LSL
	Prismatic Spread Lens	OPTD-PSL
	Snoot - Black	OPTD-SNB
	Snoot - White	OPTD-SNW
	Snoot - Silver	OPTD-SNS
	Snoot - White With Black Splay	OPTD-SNWB
	Snoot - Silver With Black Splay	OPTD-SNSB

* Other filters, colored glass, dichroics & micro-lenses available upon request

LED Performance Chart

BRIDGELUX

WATTAGE / LUMENS	CRI / COLOR	BEAM
22L 22W LED / 2200lm nom.	8027 80CRI / 2700K	N
34L 34W LED / 2800lm nom.	8030 80CRI / 3000K	Narrow 17°
	8035 80CRI / 3500K	M
	8040 80CRI / 4000K	Medium 26°
	9027 90CRI / 2700K	W
	9030 90CRI / 3000K	Wide 52°
	9727 97CRI / 2700K	
	9730 97CRI / 3000K	



CREE

WATTAGE / LUMENS	CRI / COLOR	BEAM
35C 35W LED / 2970lm nom.	8027 80CRI / 2700K	N
41C 41W LED / 3350lm nom.	8030 80CRI / 3000K	Narrow 13°
	8035 80CRI / 3500K	M
	8040 80CRI / 4000K	Medium 20°
	9527 95CRI / 2700K	W
	9530 95CRI / 3000K	Wide 44°
	9535 95CRI / 3500K	
	9540 95CRI / 4000K	

