

PROJECT	TYPE	CATALOG NUMBER
---------	------	----------------

CONFIG	A	B
11	14.78" (375)	8.21" (209)
12	21.68" (551)	8.21" (209)
13	36.27" (921)	8.21" (209)
14	43.17" (1097)	8.21" (209)
15	65.07" (1653)	8.21" (209)
16	71.98" (1828)	8.21" (209)
18	985.97" (2184)	8.21" (209)

**Lockable Double Gimbal Tilt Action**

Lockable Tilt Aiming (Tool Supplied)

Cable Grip Hardware

Power Supply Ø5" Canopy

1.50" (38)

30° 30°

14.78" (375)

8.21" (209)

Driver Enclosure

Double Gimbal LED Holder

Measurements in ( ) are metric equivalents.

## Specifications

### CONSTRUCTION

- Horizontal surface-mount suspended ceiling fixture
- All aluminum construction with powder coat finish
- 1.50" x .75" extruded frame
- .188" thick aluminum cross blades
- Perforated driver enclosure for cooler operating temperature
- Frame mounted double gimbal LED source
- Lockable 30° x 30° tilt aiming
- Powder coat finish

### LED Source

- Field-replaceable integral LED module
- Field-changeable optic
- CREE
- Accepts up to 2 or more optical accessories



### ELECTRICAL

- Field-replaceable integral LED driver
- Electrical wiring compartment integrated into housing construction
- Thermal protection
- Easy maintenance access
- Optional dimming

### MOUNTING

- Suspended ceiling mount
- 6' aircraft cable with cable grip hardware

### LABELS

- Suitable for damp location








**5 YEAR WARRANTY**  
Limited



### ORDERING INFO

SERIES	CONFIG	LED MODULE WATTAGE AND INFORMATION	CRI / COLOR	BEAM	DRIVER	FINISH	OPTIONS
<b>PNH-D</b>  <b>LARGE SUSPENDED MULTIFORMS</b> Horizontal Suspension Integral Drivers	11	CREE	8027 80CRI / 2700K	N Narrow 10°	DMU Dimming Multiple Forward/Reverse Phase (@ 120V only) 0-10V Wires Present (@ 120-277V)	BB Black WW White SS Silver	EM Remotely Mounted Emergency LED Inverter. (Intended for 1 light - Field wiring required)
	12	26C 26W LED / 2710lm	8030 80CRI / 3000K	M Medium 21°			
	13	34C 34W LED / 3299lm	8035 80CRI / 3500K				
	14	40C 40W LED / 4206lm	8040 80CRI / 4000K				
	15	Delivered @ 80CRI / 3000K Narrow Beam	9227 92CRI / 2700K				
	16		9230 92CRI / 3000K				
	18		9235 92CRI / 3500K 9240 92CRI / 4000K				
<b>PNH-D</b>							

Example: **PNH-D-12-26C-9227-N-DMU-BB-EM**

OPTICAL ACCESSORY	DESCRIPTION	LIGHT SOURCE
		MEDIUM
	Clear Lens	OPTD-CLR
	Clear Lens - LED Film	OPTD-L-CLR
	UV Lens	OPTD-UVL
	Hex Cell Louver	OPTD-HXL
	Diffusion Lens	OPTD-DFL
	Diffusion Lens - LED Film	OPTD-L-DFL
	Linear Spread Lens	OPTD-LSL
	Linear Spread Lens - LED Film	OPTD-L-LSL
	Prismatic Spread Lens	OPTD-PSL
	Snoot - Black	OPTD-SNB
	Snoot - White	OPTD-SNW
	Snoot - Silver	OPTD-SNS
	Snoot - White With Black Splay	OPTD-SNWB
	Snoot - Silver With Black Splay	OPTD-SNSB

\* Other filters, colored glass, dichroics & micro-lenses available upon request