

| | | |
|---------|------|----------------|
| PROJECT | TYPE | CATALOG NUMBER |
|---------|------|----------------|

Measurements in () are metric equivalents.



Specifications

CONSTRUCTION

- Die formed circular steel LED housing
- Molded satin acrylic lens
- Spun steel canopy and driver enclosure
- Powder coat finish

LED SOURCE

- LED strip circumferentially mounted
- 19W / 1340lm, 80CRI / 3000K - 16" Diameter
- 28W / 2050lm, 80CRI / 3000K - 24" Diameter
- 32W / 2560lm, 80CRI / 3000K - 32" Diameter
- 47W / 3295lm, 80CRI / 3000K - 48" Diameter
- 60W / 4165lm, 80CRI / 3000K - 60" Diameter

ELECTRICAL

- Field accessible junction box wiring with power supply enclosure, access from below
- Integral thermo protection
- LED driver located in Ø5" x 1.75" tall canopy

MOUNTING


- Canopy mounted directly to junction box
- Canopy, 6' aircraft cable, cable grip hardware (adjustable) and power lead

LABELS


- Suitable for damp location

RINGER SUSPENSION

**3 CABLE
CANOPY SUSPENSION**
16" RING
24" RING
32" RING
48" RING



**4 CABLE
CANOPY SUSPENSION**
60" RING



**5 YEAR
WARRANTY**
Limited



ORDERING INFO

| SERIES | WATTAGE / SIZE | CRI / COLOR | POWER SUPPLY | VOLTAGE | FINISH |
|--|--|---|--|------------------------------------|---|
| RINGER LED Pendant Circular Suspended Ambient Lighting | 19L 16" diameter 19W LED / 1340lm (@ 80CRI min / 3000K) | 8030 80CRI / 3000K (Other color temperatures available with special orders) | D1 Phase Dimming* (120V only) D2 0-10V Dimming 120-277V * Not available in 60L - 60" Ring | 1 120V U 120-277V | SS Silver (White or Black finish available with special orders) |
| | 28L 24" diameter 28W LED / 2050lm (@ 80CRI min / 3000K) | | | | |
| | 32L 32" diameter 32W LED / 2560lm (@ 80CRI min / 3000K) | | | | |
| | 47L 48" diameter 47W LED / 3295lm (@ 80CRI min / 3000K) | | | | |
| | 60L 60" diameter* 60W LED / 4165lm (@ 80CRI min / 3000K) | | | | |
| RINGER | | | | | |

Ordering Example: **RINGER-28L-8030-D1-1-SS**