



PROJECT	TYPE	CATALOG NUMBER
---------	------	----------------

Measurements in () are metric equivalents.

9801 **ROUND FLAT TRIMLESS ACCENT** - The VF150 Series is a large aperture, high efficiency family of products that meet and exceed the needs of today's lighting designers and specifiers that are seeking performance. Formed of die-cast aluminum.



(Shown with lens)

Specifications


ROUND FLAT TRIMLESS ACCENT

- Fixed or adjustable light output application
- 4.00" round die-cast aluminum
- 3.00" round large aperture
- Trimless insert
- Ball catch retainer for easy trim insertion and removal
- Safety cable included
- Powder coat finish

TRIM ORDERING INFO

TRIM SERIES	TRIM FINISH	LAY-IN LENS / FILM
9801 4.00" Round Flat Accent Die-Cast Aluminum Trimless Insert	MW White MB Black XX Custom	CL Clear lay-in lens DF Diffused lay-in film DL Diffused lay-in lens SHCL Shower rated Clear lay-in lens SHDF Shower rated Diffused lay-in film SHDL Shower rated Diffused lay-in lens
9801		

Example: **9801-MB-SHCL**



ValuDIM™


LF Illumination's new **ValuDIM™** warm dimming allows the features of warm dimming technology to be installed in fixtures and price points once thought impossible. The small footprint LED COB design uses many of our standard subassembly components and is compatible with virtually all standard dimming protocols currently available.

The LED itself maintains 95CRI typ (92CRI min) across the usable CCT range of 3000K to 2000K and dims down to around 2% visible light output. ValuDIM™ comes in three standard beam spread offerings of narrow, medium and wide.




5 YEAR WARRANTY
Limited

Measurements in () are metric equivalents.



(HVR-1AA-S)
MINI SIZED HOUSING
(FD) Fixed Downlight Only



(HVR-1BA-S)
SMALL SIZED HOUSING
(AD) Adjustable Downlight
(FD) Fixed Downlight (Also available)

Specifications

ROUND TRIMLESS HOUSING

- Housing of all steel construction
- Adjustable die cast aluminum mud ring
- Black powder coat finish
- **Ceiling Cut-out - Ø6.50"**

ELECTRICAL

- Field-replaceable integral LED driver
- Electrical wiring compartment integrated into housing construction
- Internal thermal protection
- Easy maintenance access through ceiling opening
- Rated for through-branch wiring
- Dimmable

MOUNTING

- Butterfly brackets for commercial installation in drywall and other mud in ceiling types
- Perforated plate adjusts for 1/2", 5/8", 3/4" & 1.0" ceiling thickness
- Includes heavy-duty **L-Bars™** hanger bar system for residential installation

LABELS







- Suitable for damp location, except when ordered with shower trim - Suitable for wet location
- **Air-Tight / IC Optional**



HOUSING ORDERING INFO

SERIES	LED MODULE WATTAGE AND INFORMATION	CRI / COLOR	BEAM	HOUSING TYPE	DRIVER	VOLTAGE	OPTIONS
HVR-1AA-S Mini Round Trimless New Construction Housing	BRIDGELUX 11L 11W LED / 825lm nom. 16L 16W LED / 1100lm nom.	8027 80CRI / 2700K Bridgelux / CREE	BRIDGELUX N Narrow 20° M Medium 28° W Wide 40° V Very Wide 74°	FD Fixed AD Adjustable*	D1 Phase Dimming (120V only) D2 0-10V Dimming (120-277V only) D3 Lutron Hi-lume™™ Forward Phase (120V only) D4 Lutron Hi-lume™™ EcoSystem™™ & 3 wire 1% (120-277V only) DE Lutron Hi-lume™™ EcoSystem™™ 1% with Soft-On, Fade-to-Black™™ 1% (120-277V only) * Not available in HVR-1AA-T mini housing	1 120V 2 277V U 120-277V*	IC Insulated Ceiling (Not Available in 28C) EM Remotely Mounted Emergency LED Inverter
		8030 80CRI / 3000K Bridgelux / CREE					
		8035 80CRI / 3500K Bridgelux / CREE					
HVR-1BA-S Small Round Trimless New Construction Housing	CREE 09C 09W LED / 900lm nom. 14C 14W LED / 1200lm nom. 20C 20W LED / 1600lm nom.* 28C 28W LED / 2200lm nom.* *HVR-1BA-S Small housing only	9027 90CRI / 2700K Bridgelux Only	CREE N Narrow 16° M Medium 28° W Wide 42° V Very Wide 73°	* HVR-1BA-S Small housing only			
		9030 90CRI / 3000K Bridgelux Only					
		9727 97CRI / 2700K Bridgelux Only					
		9730 97CRI / 3000K Bridgelux Only					
		9527 95CRI / 2700K CREE Only					
		9530 95CRI / 3000K CREE Only					
		9535 95CRI / 3500K CREE Only					
9540 95CRI / 4000K CREE Only							
Black finish is standard	ValuDIM™ 15V 15W LED / 810lm nom. 3000-2000K Warm Dimming	9220 92CRI / 3000-2000K Warm Dimming ValuDIM Only	ValuDIM™ N Narrow 17° M Medium 25° W Wide 38°				

Example: **HVR-1BA-S-14C-8027-N-FD-D2-U-IC**

OPTICAL ACCESSORY	DESCRIPTION	LIGHT SOURCE
		MINI / SMALL
		<ul style="list-style-type: none"> • MR16 • CMHMR16 • 50mm LED
	Clear Lens	OPTB-CLR Ø2.00" (51mm) nom.
	Clear Lens - LED Film	OPTB-L-CLR Ø2.00" (51mm) nom.
	UV Lens	OPTB-UVL Ø2.00" (51mm) nom.
	Hex Cell Louver	OPTB-HXL Ø2.00" (51mm) nom.
	Diffusion Lens	OPTB-DFL Ø2.00" (51mm) nom.
	Diffusion Lens - LED Film Diffusion Lens is included on all Luminaires installed with ValuDIM (15C9220) sources	OPTB-L-DFL Ø2.00" (51mm) nom.
	Linear Spread Lens	OPTB-LSL Ø2.00" (51mm) nom.
	Linear Spread Lens - LED Film	OPTB-L-LSL Ø2.00" (51mm) nom.
	Prismatic Spread Lens	OPTB-PSL Ø2.00" (51mm) nom.

* Other filters, colored glass, dichroics & micro-lenses available upon request